



## 2025 Crown Vic Rules

**The creation of an affordable, entry level way to enter stock car racing.  
Keeping the cars stock is the priority of this division.**

**Only Ford Crown Vic, Mercury Grand Marquis, or Lincoln  
Town Car 1992 or newer.**

### **1. BODY**

- 1.1- Remove all glass and trim.
- 1.2- Remove headlights and taillights.
- 1.2-1- may cover with sheet metal.
- 1.3- Doors must be welded.
- 1.4- Hood and trunk must have a minimum of 2 hood pins.
- 1.4-1- locks must be removed.
- 1.5- Stock steering column, may use a quick disconnect steering wheel.
- 1.6- Dash may be removed and replaced with sheet metal.
- 1.7- All airbags must be removed.
- 1.8- May replace front bumper with all-star part  
#ALL22352 or same

### **2. SUSPENSION**

- 2.1- Stock for make and model.
- 2. 2-All replaced parts must be OEM replacement or same stock parts only.
- 2.3- May adjust as factory adjustments allow only.
- 2.4- Spring must be stock, identical side to side, with ½' tolerance on overall uncompressed height between the 2 sides.
- 2.5- No air ride allowed.
- 2.6- Front and rear sway bar must remain as from the factory with factory links or may remove front and rear completely.

### **3. WHEELS & TIRES**

3.1- Stock steel or aluminum wheels only. (no racing wheels) 3.1-1-

All 4 must be the same size and offset.

3.2- These tire sizes only 235/55/17, 225/60/16, and 215/70/15.

3.2- All season tires only. No performance or directional allowed.

### **4. ENGINE**

4.1- Must remain entirely stock 4.6L SOHC engine.

4.2- Pump gas only. (fuel kill switch may be relocated or kill all switch added)

### **5. TRANSMISSION**

5.1- Must remain entirely stock.

### **6. REAR END**

6.1- Must remain entirely stock

6.2- Factory 3.73 gear ratio max.

6.3- Factory posi or weld the spider gear. (No aftermarket lockers)

### **7. ROLL CAGE & SAFETY**

7.1- Must have seamless tubing 4-point roll cage only with X braced hoop behind driver with minimum of 3 door bars with vertical bracing from top to bottom. Cage must be 1.5" x .095" tubing. Frame must have minimum 1/4 -inch steel plate welded to frame where bars connect.

7.2- Approved racing seat and 5-point harness. Must be safely secured to the roll cage.

7.3- Working fire extinguisher or fire suppression system.

7.4- Properly mounted window net.

7.5- Battery may remain in stock location or moved behind driver, must be securely mounted, and covered if moved.

7.6- Radiator must contain water only.

7.7- 2-1/2" max exhaust pipe run to passenger side or to rear. May remove catalytic converter.

### **PROTEST & CLAIM**

- Visual protest only- \$25 - Must be done 30 mins before the race starts.
- Protest 3 items for \$300, \$100 acceptance, track keeps \$100
- Engine or Transmission Claim -\$700 (no bolt ons) track keeps \$100 - \$500 buy back

- ECU Claim-\$125 - \$75 buy back